



Material Safety Data Sheet

Material Name: ULTRABOND ECO 20

ID: NDM0008

*** Section 1 - Chemical Product and Company Identification ***

Material Name: ULTRABOND ECO 20

Product Use

Flooring adhesive

Manufacturer Information

USA and Puerto Rico

MAPEI

1144 East Newport Center Drive

Deerfield Beach, FL 33442

Phone: 1-954-246-8888

Canada

MAPEI

2900 Francis-Hughes Avenue

Laval, QC H7L 3J5

Phone: 1-450-662-1212

IN THE EVENT OF A CHEMICAL EMERGENCY INVOLVING A SPILL, LEAK, FIRE, EXPLOSION, EXPOSURE OR ACCIDENT, CONTACT THE FOLLOWING NUMBERS:

Emergency 24 hour numbers:

(USA) CHEMTREC 1-800-424-9300

(Canada) CANUTEC 1-631-996-6666

*** Section 2 - Hazards Identification ***

Emergency Overview

This product has been evaluated using criteria specified in 29CFR 1910.1200 (Hazard Communication Standard).

This product is irritating to the eyes.

Hazard Statements

CAUTION! IRRITANT. Irritating to eyes. Wear suitable gloves and eye/face protection. Keep out of the reach of children.

Potential Health Effects: Eyes

This product is irritating to the eyes.

Potential Health Effects: Skin

This product may cause irritation to the skin.

Potential Health Effects: Ingestion

Acute ingestion may result in mild gastrointestinal distress.

Potential Health Effects: Inhalation

This product may cause irritation to the respiratory system.

Medical Conditions Aggravated by Exposure

Hypersensitivity to product, allergies, and skin or respiratory disorders

Potential Environmental Effects

None identified.

HMIS Ratings: Health: 1 Fire: 0 Reactivity: 0 Pers. Prot.: Safety glasses, gloves

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

*** Section 3 - Composition / Information on Ingredients ***

| CAS # | Component | Percent |
|-------|-----------|---------|
|-------|-----------|---------|

Material Safety Data Sheet

Material Name: ULTRABOND ECO 20

ID: NDM0008

| | | |
|------------|--|-------|
| 1317-65-3 | Limestone | 15-40 |
| 1332-58-7 | Kaolin | 7-13 |
| 64742-52-5 | Naphthenic oil | 7-13 |
| 57-13-6 | Urea | 1-5 |
| 8050-26-8 | Resin acids and Rosin acids, esters with pentaerythritol | 1-5 |

*** Section 4 - First Aid Measures ***

First Aid: Eyes

Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists, get medical attention.

First Aid: Skin

Flush with large amounts of water. If irritation persists, get medical attention.

First Aid: Ingestion

Flush out mouth with water. If ingestion of a large amount does occur, seek medical attention. Do not induce vomiting.

First Aid: Inhalation

Immediately remove the affected person to fresh air. If symptoms persist, get medical attention.

First Aid: Notes to Physician

Provide general supportive measures and treat symptomatically.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.

This product is an aqueous mixture which will not burn. If evaporated to dryness, the solid residue may pose a slight fire hazard.

Hazardous Combustion Products

Irritating and toxic gases or fumes may be released during a fire. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical (preferred), foam, water.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Containment Procedures

Dike the spilled material, where this is possible. Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps. Scoop up used absorbent into drums or other appropriate container.

Personal Precautions

Wear appropriate protective equipment and clothing during clean-up.

Clean-Up Procedures

Attempt to reclaim the free product, if this is possible. Shovel the material into waste container. Thoroughly wash the area with water after a spill or leak clean-up. Wear appropriate protective equipment and clothing during clean-up.

Material Safety Data Sheet

Material Name: ULTRABOND ECO 20

ID: NDM0008

Environmental Precautions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Evacuation Procedures

None identified.

Special Procedures

Regulations vary. Consult local authorities before disposal.

*** Section 7 - Handling and Storage ***

Handling Procedures

Avoid getting this material into contact with your skin and eyes. Use this product with adequate ventilation. Wash hands after handling and before eating. Keep out of the reach of children.

Storage Procedures

Store at ambient temperature and atmospheric pressure. Store away from strong oxidizers.

*** Section 8 - Exposure Controls / Personal Protection ***

A: Component Exposure Limits

Limestone (1317-65-3)

| | |
|-------------------|---|
| OSHA: | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) |
| NIOSH: | 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust) |
| Alberta: | 10 mg/m3 TWA |
| British Columbia: | 10 mg/m3 TWA (total dust); 3 mg/m3 TWA (respirable fraction) 20 mg/m3 STEL |
| New Brunswick: | 10 mg/m3 TWA (particulate matter containing no asbestos and < 1% crystalline silica) |
| NW Territories: | 5 mg/m3 TWA (respirable mass); 10 mg/m3 TWA (total mass) |
| Nunavut: | 5 mg/m3 TWA (respirable mass); 10 mg/m3 TWA (total mass) |
| Quebec: | 10 mg/m3 TWAEV (total dust, containing no asbestos and less than 1% crystalline silica) |
| Saskatchewan: | 20 mg/m3 STEL 10 mg/m3 TWA |
| Yukon: | 20 mg/m3 STEL 30 mppcf TWA; 10 mg/m3 TWA |

Kaolin (1332-58-7)

| | |
|-------------------|---|
| ACGIH: | 2 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction) |
| OSHA: | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) |
| NIOSH: | 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust) |
| Alberta: | 2 mg/m3 TWA (respirable) |
| British Columbia: | 2 mg/m3 TWA (particulate matter containing no asbestos and less than 1% crystalline silica, respirable particulate) |
| Manitoba: | 2 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction) |
| New Brunswick: | 2 mg/m3 TWA (particulate matter containing no asbestos and < 1% crystalline silica, respirable fraction) |
| NW Territories: | 5 mg/m3 TWA (respirable mass); 10 mg/m3 TWA (total mass) |
| Nova Scotia: | 2 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction) |
| Nunavut: | 5 mg/m3 TWA (respirable mass); 10 mg/m3 TWA (total mass) |
| Ontario: | 2 mg/m3 TWAEV (containing no asbestos and less than 1% crystalline silica, respirable) |
| Quebec: | 5 mg/m3 TWAEV (respirable dust, containing no asbestos and less than 1% crystalline silica) |
| Saskatchewan: | 4 mg/m3 STEL (respirable fraction) 2 mg/m3 TWA (respirable fraction) |
| Yukon: | 20 mg/m3 STEL 30 mppcf TWA; 10 mg/m3 TWA |

Engineering Controls

Use general ventilation.

Material Safety Data Sheet

Material Name: ULTRABOND ECO 20

ID: NDM0008

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses with side shields.

Personal Protective Equipment: Skin

The use of nitrile-latex gloves is recommended.

Personal Protective Equipment: Respiratory

Not normally needed. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Personal Protective Equipment: General

Launder contaminated clothing before reuse. Use good industrial hygiene practices in handling this material.

*** Section 9 - Physical & Chemical Properties ***

| | | | |
|--|-------------|--|---------------------|
| Appearance: | Beige paste | Odor: | Slight acrylic odor |
| Physical State: | Paste | pH: | 7-11 |
| Vapor Pressure: | N/A | Vapor Density: | N/A |
| Boiling Point: | N/A | Melting Point: | N/A |
| Solubility (H2O): | N/A | Specific Gravity: | 1.2 - 1.5 |
| Evaporation Rate: | N/A | VOC: | 18 g/L |
| Octanol/H2O Coeff.: | N/A | Flash Point: | >200° F |
| Flash Point Method: | CC | Upper Flammability Limit (UFL): | N/A |
| Lower Flammability Limit (LFL): | N/A | Burning Rate: | N/A |
| Auto Ignition: | N/A | | |

Physical Properties: Additional Information

The data provided in this section is to be used for product safety handling purposes. Please refer to Product Data Sheets, Certificates of Conformity or Certificates of Analysis for chemical and physical data for determinations of quality and for formulation purposes.

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

This is a stable material.

Chemical Stability: Conditions to Avoid

Do not freeze.

Incompatibility

This product may react with strong oxidizing agents.

Hazardous Decomposition

Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Possibility of Hazardous Reactions

Will not occur.

*** Section 11 - Toxicological Information ***

Acute Dose Effects

A: General Product Information

No information available for the product.

B: Component Analysis - LD50/LC50

Naphthenic oil (64742-52-5)

Material Safety Data Sheet

Material Name: ULTRABOND ECO 20

ID: NDM0008

Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg
Urea (57-13-6)
Oral LD50 Rat 8471 mg/kg

Carcinogenicity

A: General Product Information

No information available for the product.

B: Component Carcinogenicity

Kaolin (1332-58-7)

| | |
|--------|---|
| ACGIH: | A4 - Not Classifiable as a Human Carcinogen |
|--------|---|

Sensitization

No information available for the product.

*** Section 12 - Ecological Information ***

Ecotoxicity

A: General Product Information

No information available for the product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Naphthenic oil (64742-52-5)

| Test & Species | | Conditions |
|--------------------------------|------------|------------|
| 96 Hr LC50 Oncorhynchus mykiss | >5000 mg/L | |
| 48 Hr EC50 Daphnia magna | >1000 mg/L | |

Urea (57-13-6)

| Test & Species | | Conditions |
|---------------------------------|--------------------|------------|
| 96 Hr LC50 Poecilia reticulata | 16200-18300 mg/L | |
| 24 Hr EC50 Daphnia magna Straus | >10000 mg/L | |
| 48 Hr EC50 Daphnia magna | 3910 mg/L [Static] | |

*** Section 13 - Disposal Considerations ***

US EPA Waste Number & Descriptions

A: General Product Information

No additional information available.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

*** Section 14 - Transportation Information ***

International Transportation Regulations

Not regulated as dangerous goods.

Material Safety Data Sheet

Material Name: ULTRABOND ECO 20

ID: NDM0008

*** Section 15 - Regulatory Information ***

US Federal Regulations

A: General Product Information

All of the components of this product are listed on, or are exempted from listing on the U.S. EPA TSCA Inventory of Chemical Substances. All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List unless otherwise noted.

B: Component Analysis

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

State Regulations

A: General Product Information

Other state regulations may apply. Check individual state requirements.

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

| Component | CAS | CA | MA | MN | NJ | PA | RI |
|-----------|-----------|----|-----|-----|-----|-----|-----|
| Limestone | 1317-65-3 | No | Yes | Yes | Yes | Yes | Yes |
| Kaolin | 1332-58-7 | No | Yes | Yes | Yes | Yes | Yes |
| Urea | 57-13-6 | No | No | Yes | No | No | No |

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains a chemical known to the state of California to cause cancer. This product contains a chemical known to the state of California to cause reproductive/developmental effects.

Canadian WHMIS Information

A: General Product Information

Not regulated

B: Component Analysis - WHMIS IDL

No components are listed in the WHMIS IDL.

Additional Regulatory Information

A: General Product Information

Supplier(s) of proprietary component(s) state that these components are contained on the TSCA inventory.

B: Component Analysis - Inventory

| Component | CAS # | TSCA | CAN | EEC |
|--|------------|------|------|--------|
| Limestone | 1317-65-3 | Yes | NDSL | EINECS |
| Kaolin | 1332-58-7 | Yes | DSL | EINECS |
| Naphthenic oil | 64742-52-5 | Yes | DSL | EINECS |
| Urea | 57-13-6 | Yes | DSL | EINECS |
| Resin acids and Rosin acids, esters with pentaerythritol | 8050-26-8 | Yes | DSL | EINECS |

*** Section 16 - Other Information ***

Reference

15-2550-57

Material Safety Data Sheet

Material Name: ULTRABOND ECO 20

ID: NDM0008

Other Information

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

Key/Legend

NA = Not available or Not Applicable. NFPA = National Fire Protection Association. HMIS = Hazardous Material Information System. CFR = Code of Federal Regulations. EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration., NJTSR = New Jersey Trade Secret Registry.

Contact: Product Safety Specialist

Contact Phone: 1-954-246-8888

End of Sheet NDM0008