

HAZARD RATING

4=EXTREME
 3=HIGH
 2=MODERATE
 1=SLIGHT
 0=INSIGNIFICANT

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0

MATERIAL SAFETY DATA SHEET
VEXCON NO. CP116A



Performance Construction Chemicals

7240 STATE RD • PHILADELPHIA, PA 19135
 VOICE: 215.332.7709 • FAX: 215.332.9997
 TOLL FREE: 888-VEXCON-1
 WEBSITE ADDRESS: www.vexcon.com

GENERAL INFORMATION

PRODUCT IDENTIFICATION: MOISTUREBLOC REDUCTION PRIMER
 STEP 1 FT

VOC CONTENT: 296 GR/LITER OR 2.47# /GAL

CATEGORY: CONCRETE PROTECTIVE COATING EPA OR
 MASTIC TEXTURE COATING AIM

COMMON NAME: WATERPROOFING CONCRETE SEALER

DOT SHIPPING NAME: IN CONTAINERS LESS THAN 119 GALS.:
 MOISTUREBLOC REDUCTION PRIMER STEP 1 FT(NON-REGULATED)
 IN CONTAINERS GREATER THAN 119 GALS: COMUSTIBLE LIQUID,
 N.O.S.(AROMATIC SOLENT), , NA1993.III

FOR LIMITED QUANTITY AIR & OCEAN SHIPMENT: RQ (ACETONE)
 RESIN SOLUTION, FLAMMABLE, 3, UN1866, III

HEALTH AND SAFETY: THIS IS A SOLVENT BASED PRODUCT: USE ONLY
 WITH ADEQUATE VENTILATION; IF SWALLOWED, DO NOT INDUCE
 VOMITING; USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND
 OTHER PROTECTIVE CLOTHING IS ADVISED WHEN HANDLING THIS
 PRODUCT.

SECTION I

MANUFACTURER: VEXCON CHEMICALS
EMERGENCY NO: 1-800-858-2828
CHEMTREC NO: 1-880-424-9300
TELEPHONE NO: 1-215-332-7709
ADDRESS: 7240 STATE RD., PHILA., PA 19135
PREPARED: NOVEMBER 1996
UPDATED: JANUARY 2006
PREPARED BY: DARRYL F. MANUEL/PRESIDENT

SECTION II HAZARDOUS INGREDIENTS

<u>MATERIAL OR COMPONENTS</u>	<u>CAS#</u>	<u>%</u>	<u>HAZARD DATA</u>	<u>UN#</u>
PIGMENTS:				
1. TITANIUM DIOXIDE	13463-67-7	> 1%	RESPIRABLE DUST 5mg/M3 TLV 5 mg/M3 TOTAL DUST 15 mg/M3 TLV 10 mg/M3	
2. CALCIUM CARBONATE	1317-65-3	> 1%	SAME AS ABOVE	
VINYL TOLUENE STYRENE ACRYLATE POLYMER	25085-34-1	17%	NA	
STODDARD SOLVENT BALANCE INERT FILLERS	8052-41-3	20%	TLV 100 PPM	1255

THIS PRODUCT DOES NOT CONTAIN ANY SECTION 313 REPORTABLE
 INGREDIENTS.

**SECTION III PHYSICAL/CHEMICAL
 CHARACTERISTICS**

BOILING POINT: 310-495° F **MELTING POINT:** N/A
SPECIFIC GRAVITY 1.48 **VAPOR PRESSURE:** 200 mm Hg 68° F
VAPOR DENSITY (AIR=1): APPROX. 5 **% VOLATILES BY**
SOLUBILITY IN H2O % BY WT: SOLUBLE
EVAPORATION RATE (BUAC=1): 0.1 N/A
 PH (AS IS) 8.5-9.5 PH (1% SOLN.)
APPEARANCE AND ODOR: VERTY THICK PAINT, VARIOUS COLORS,
 SLIGHTLY SWEET PETROLEUM ODOR

SECTION IV FIRE AND EXPLOSION DATA

FLASH POINT: (TEST METHOD): 106° F TCC
AUTOIGNITION TEMPERATURE: 473
FLAMMABLE LIMITS IN AIR: % BY VOL: LOWER: 0.7 UPPER: 6.0
EXTINGUISHING MEDIA: EXCLUDE AIR-USE FOAM CO2, STEAM,
 WATER, FOG, DRY CHEMICALS.
SPECIAL FIRE FIGHTING PROCEDURES: THE USE OF SELF CONTAINED
 BREATHING APPARATUS IS RECOMMENDED FOR FIRE FIGHTERS.
 SEE ALSO SECTION IX.
UNUSUAL FIRE AND EXPLOSION HAZARD: NO UNUSUAL HAZARDS
 KEEP WORK AREAS FREE OF HOT METAL AND OTHER SOURCES OF
 IGNITION.

SECTION V REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY: PRODUCT IS STABLE
INCOMPATIBILITY: THIS PRODUCT IS INCOMPATIBLE WITH STRONG
 OXIDIZING AGENTS. STRONG ACIDS OR BASES AND SELECTED AMINES.
HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITION
 IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND
 UNIDENTIFIED ORGANICS.
CONDITIONS CONTRIBUTING TO HAZARD POLYMERIZATION: N/A
 WILL NOT OCCUR.

GENERAL HAZARD: COMBUSTIBLE LIQUID, CAN FORM COMBUSTIBLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. STATIC DISCHARGE, MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT WELD, BRAZE, SOLDER DRILL GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY DISPOSED OF.

ELECTROSTATIC ACCUMULATION HAZARD: USE PROPER GROUNDING

SECTION VI HEALTH HAZARD INFORMATION

HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR CLASSIFICATION

ROUTES OF EXPOSURE: THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES, DIZZINESS, LIGHT HEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION. MINERAL SPIRITS COMPONENTS.

SKIN CONTACT: THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT.

SKIN ABSORPTION: SEE ABOVE

EYE CONTACT: THIS PRODUCT MAY BE AN EYE IRRITANT. MINERAL SPIRITS COMPONENT.

EFFECTS OF OVEREXPOSURE TLV - 100 PPM

ACUTE OVEREXPOSURE: ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES CONSULT A PHYSICIAN.

SKIN: IMMEDIATELY WASH SKIN WITH SOAP AND PLENTY OF WATER. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

INHALATION: MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.

INGESTION: DO NOT INDUCE VOMITING, SEEK PROMPT MEDICAL ATTENTION.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

AQUATIC TOXICITY (E.G. 96 HR. TLM):

WASTE DISPOSAL METHOD: IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, STATE, AND LOCAL REGULATIONS.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: IF POSSIBLE PUMP TO CONTROLLED CONTAINMENT AREA. ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES, INCLUDING PILOT LIGHTS, ELECTRICAL SPARKS). PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP IS COMPLETE. STOP SPILL AT SOURCE. DIKE SPILL AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID CAN BE TAKEN UP ON SAND, EARTH, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND SHOVEL INTO CONTAINERS.

SECTION VIII CONTROL MEASURES

VENTILATION REQUIREMENTS: LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

RESPIRATORY(SPECIFY IN DETAIL): CHEMICAL CARTRIDGE RESPIRATOR; HALF MASK ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.

EYES: CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION, OR INJURY.

GLOVES: IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.

OTHER CLOTHING AND EQUIPMENT: TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS ARE RECOMMENDED.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONARY STATEMENTS:

PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED AND DRIED BEFORE RE-USE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED, SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.

OTHER HANDLING AND STORAGE REQUIREMENTS:

STORE IN WELL VENTILATED AREA. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK OR TOBACCO IN AREA WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

HMIS HAZARD RATINGS:

	NPCA-HMIS	NFPA 70	KEY
HEALTH	1	1	4=SEVERE
FLAMMABILITY	1	1	3=SERIOUS
REACTIVITY	0	0	2=MODERATE 1=SLIGHT 0=MINIMAL

ADDITIONAL REGULATORY CONCERNS: (FEDERAL, FDA, USDA, CPSC, STATE, OTHER)

FEDERAL:

FDA:

USDA:

TSCA: IS THIS PRODUCT, OR ALL IT'S INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES

PREPARED BY: DARRYL MANUEL

TITLE: PRESIDENT

COMPANY: VEXCON CHEMICALS

ADDRESS: 7240 STATE RD., PHILA., PA 19135

THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETMENT OF THE INFORMATION CONTAINED HEREIN.